


Below is typically how an **EZS** is wired from the car to the **EZS**.



INSTALLATION:

To make a good job, ensure that the **NEC PRO KEY V2** is fitted as far back as possible.

To use the **NEC PRO KEY V2** all you need to do is to locate the **GREEN** & **GREEN/WHITE** cable which leads in to the **EZS** plug. These are normally paired together.

Cut the GREEN wire first , then cut the GREEN/WHITE wire. Connect as in diagram below, once you have connected the GREEN+GREEN/WHITE wires to the NEC PRO KEY V2, connect the BROWN , RED wires last.

The LED on the NEC PRO KEY V2 should light up.

Look at the diagram below, and wire in according to the model that you have.



WIRING COLOURS:

Most Mercedes **EZS** have the same coloured wires going in, if for any reason you cannot find the wires for the **RED** and **BROWN**, then follow the table below:

NEC PRO KEY V2	W212 (E-CLASS)	W221 (S-CLASS)	W204 (C-CLASS)
RED	RED/BLUE STRIPE	PLUG A – PIN 6 RED	PLUG C – PIN1 RED
BROWN	THICK BROWN on 2 nd plug	PLUG A – PIN 2 BROWN	PLUG B –PIN10 BROWN

(This version is not compatible with : ML W164 – GL X164 – R W251)

CONCLUSION:

Cut the **GREEN** wire going to the **EZS** and connect the SOLID GREEN from the Pro Key.

Cut the GREEN/WHITE going to the **EZS** and connect the SOLID WHITE from the Pro Key.

The other end of the **GREEN** from the vehicle side connects to the **SOLID BLACK** from the Pro Key.

The other end of the GREEN/WHITE from the vehicle side connects to the BLACK/WHITE from the Pro Key.

Connect the **SOLID RED** from the Pro Key to the **RED** to the **EZS** , do not cut just join to the cable.

Connect the **SOLID BROWN** from the Pro Key to the **BROWN** to the **EZS** , do not cut just join to the cable.